



NOTES:-

- HOT DIP GALVANIZED PER ASTM A-153.
- SHAFT MATERIAL - HOT ROLLED RCS (ROUND CORNERED SQUARE) SOLID STEEL BARS; MINIMUM YIELD STRENGTH 90KSI.
- MINIMUM TENSILE STRENGTH - 70 KIP
- PULLING EYE RATED 12,000 LBS
- COMES WITH $3/4"$ X $3"$ A325 GALVANIZED STRUCTURAL BOLT AND $3/4"$ A563 GRADE A GALVANIZED JAM NUT
- SOCKET IS UPSET FORGED
- ALL DIMENSIONS ARE IN INCHES UNLESS OTHER SPECIFIED



THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION AND IS THE EXCLUSIVE PROPERTY OF ORBIS MANUFACTURING

ORBIS

DRAWN	MSM	DATE	02-02-2023
APPROVED	DMM	DATE	12-02-2023
REVISION	1		

DRAWING NUMBER

ARCS15ADTE-7K

DESCRIPTION

ANCHOR ADAPTER TRIPLE EYE THIMBLE
18" 7K FT-LB 70K LBS TENSILE INCL 12K
LBS EYE 1.5" RCS SHAFT